Technické parametry – Amiko HD8260+

Tuner & Demodulation
Tuner Type: DVB-S / DVB-S2
Input Connector: F-type, Connector, Female
Signal Level: -65 to -25 dBm
LNB Power & Polarization: Vertical: +13V/+14V, Horizontal: +18V/+19V
Current: Max. 400mA (Overload Protection)
22KHz Tone Frequency: 22±1KHz
DiSEqC Control: Version 1.0, 1.1, 1.2, USALS
Demodulation: QPSK, 8PSK
Input Symbol Rate: 2-45 Mbps,
FEC: 1/2, 2/3, 3/4, 5/6, 7/8 and Auto

Tuner Type: DVB-T2 / DVB-C
Frequency Range: 48~862MHz
RF Input Level: -80dBm to -20dBm
Antenna power output: DC 5V at max 75mA, Overload protection
Demodulation: COFDM 1K, 2K, 4K, 8K normal and extended, 16K normal and extended, 32K normal and extended
Input Symbol Rate: 1.0 ~ 7.0Ms/s
Constellations: QPSK, 16QAM, 64QAM, 256QAM / Both rotated and non-rotated
Guard Intervals: 1/4, 19/256, 1/8, 19/128, 1/16, 1/32, 1/128
Code Rate: 1/2, 3/5, 2/3, 3/4, 5/6

System Resources
Main Processor: Dual Core 600MHz CPU
Flash Memory: 16MB
DDR3 RAM: 256MB

MPEG TS A/V Decoding
Transport Stream: MPEG-2, H.264
Input Rate: Max.120Mbit/s
Aspect Radio: 4:3, 16:9, Letter Box
Video Decoding: MPEG-2, MP@ML, MPEG-4 part 10/H264
Video Resolution: 720*480P/I, 720*576P/I, 1280*720p, 1920*1080i, 1920*1080p
Audio Decoding: MPEG-1 layer I/II, MPEG-2 layer II, Dolby digital
Audio Mode: Left / Right / Stereo/ Mono
Sampling Rate: 32, 44.1 and 48KHz

Power Supply
Input Voltage: Free Voltage (100-250V AC 50/60Hz)
Power Consumption: 30W Max
Stand-By Power Consumption: <0.5W

A/V & Data Input/Output
RCA A/V: Video CVBS output, Audio L/R output
RS-232C: Transfer rate 115.2Kbps, 9 pin D-sub Type
USB: Two USB 2.0 slots
S/PDIF: Optical
HDMI: VER1.4, Type A
Ethernet: 10/100M RJ45
0/12V: 50mA max

Physical Specifications
Size[W*H*D]: 220mm*40mm*160mm
Net Weight: 1.0KG
Operation Temperature: 0°C~+45°C
Storage Temperature: -10°C~+70°C
Storage Humidity: 5%~95% RH (Non-Condensing)